























Product (front)										Product (front)			
Product (back)										Product (back)			
Product model	WN604	WG103	WN203	WNAP210	WNAP320	WNDAP350	WNDAP360	WNDAP620	WNDAP660	Product Model	WMS5316	WC7520	
Product description	Wireless-N 150 Access Point	ProSAFE® 802.11g Wireless Access Point	ProSAFE Wireless-N Standalone Access Point	ProSAFE Wireless-N Access Point	ProSAFE Wireless-N Access Point	ProSAFE Wireless-N Dual Band Access Point	ProSAFE Wireless-N Dual Band Access Point	ProSAFE Wireless-N Dual Band Premium Access Point	ProSAFE Wireless-N Dual Band Premium Access Point	Product Description	ProSAFE 16-AP Wireless Management System	ProSAFE 20-AP Wireless Controller	
Typical deployment	Small and home office	Motels, warehouse, clinics	Small office/home office, small motels, dental offices/clinics	Entry level small to medium enterprise	Small to medium enterprise, K-12 with basic WiFi	Warehouses, transportation, hardened locations	Small to medium enterprise, K-8 school with advanced WiFi, hotels, mid-size hospitals	Medium enterprise, high schools with advanced WiFi, hotels, mid-size hospitals	Medium enterprise, high schools with advanced WiFi, hotels, mid-size hospitals	Typical Deployment	Small and medium enterprise with basic WiFi, dental offices, clinics	Medium enterprise with advanced WiFi, K-12, small hotels/motels, small hospitals	
WIRELESS										HARDWARE			
Standard	802.11 b/g/n	802.11b/g	802.11 b/g/n	802.11 b/g/n	802.11 b/g/n	802.11 a/b/g/n	802.11 a/b/g/n	802.11 a/b/g/n	802.11 a/b/g/n	# of Ethernet Ports	4	4	
Single band	•	•	•	•	•					Speed of Ethernet Ports	10/100/1000 Mbps	10/100/1000 Mbps	
Dual band						• (concurrent)	• (concurrent)	• (selectable)	• (concurrent)	Physical Size	330 x 430 x 209 mm	261 x 430 x 440 mm	
2.4 GHz	•	•	•	•	•	•	•	•	•	SUPPORTED AP			
5 GHz						•	•	•	•	WNDAP660		future	
TX by Rx	1 x 1		2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	3 x 3	3 x 3	WNDAP620		future	
Throughput per radio	150 Mbps	108 Mbps	300 Mbps	300 Mbps	300 Mbps	300 Mbps	300 Mbps	450 Mbps	450 Mbps	WNDAP360	•	•	
Max # of concurrent clients (standalone)	30	30	30	30	64	128	128	128	256	WNDAP350	•	•	
Max # of concurrent clients (controller managed)				64	64	128	128	64	128	WNAP320	•	•	
										WNAP210	•	•	
										WG103	•		
HARDWARE										CAPACITY			
# of ethernet ports	4	1	1	1	1	1	1	1	2	# of managed AP	16	150	
Speed of ethernet ports	10/100 Mbps	10/100 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	Stacking		•	
PoE		•	•	•	•	•	•	•	•	# of units per stack		3	
Antenna type	detachable	detachable	internal	internal	internal	internal	internal	internal	internal	MANAGEMENT			
Antenna gain	5 dBi	3 dBi	3 dBi	5 dBi	5 dBi	5 dBi	5 dBi	5 dBi	5 dBi	HTTP	•	•	
Additional external antenna connectors			two 2.4 GHz reverse SMA		two 2.4 GHz reverse SMA	two 2.4 GHz reverse SMA	two 2.4 GHz reverse SMA	three 2.4 GHz reverse SMA	three 2.4 GHz reverse SMA	SNMP	•	•	
Plenum		•				•				Telnet	•	•	
Physical size	175 • 118 • 28 mm	158 • 101 • 29mm	224 • 153 • 28 mm	224 • 153 • 28 mm	254 • 254 • 55 mm	32 • 190 • 124 mm	254 • 254 • 55 mm	254 • 254 • 55 mm	254 • 254 • 55 mm	SSH	•	•	
Enclosure material	Plastic	Metal	Plastic	Plastic	Plastic	Metal	Plastic	Plastic	Plastic	FEATURES			
Kensington lock		•	•	•	•	•	•	•	•	Central configuration	•	•	
Ceiling/wall mounting		•	•	•	•	•	•	•	•	Multiple SSIDs, VLANs	•	•	
Power consumption	5W	5W	5.8W	5.8W	5.8W	12.7W	12.7W	8W	11.7W	Automatic RF management	Scheduled	Dynamic	
MANAGEMENT										Predeployment RF planning			
Deployment options	standalone only	standalone	standalone	standalone & controller	standalone & controller	standalone & controller	standalone & controller	standalone & controller**	standalone & controller**	Postdeployment RF calibration with heatmap			
Web UI	•	•	•	•	•	•	•	•	•	Self healing wireless network			
CLI		•	•	•	•	•	•	•	•	Dynamic load balancing			
Manageable by WMS5316		•						•**	•**	L2 and L3 fast roaming			
Manageable by WC7520				•	•	•	•	•**	•**	Built-in AAA server, LDAP support			
SSH		•	•	•	•	•	•	•	•	Captivel portal with guest management			
SNMP		•	•	•	•	•	•	•	•	Warranty	Lifetime	Lifetime	
FEATURES										Product ordering SKU			
# of BSSIDs	1	8	8	8	8	16	16	8	16	10 AP license ordering SKU			
WEP	•	•	•	•	•	•	•	•	•	Price			
WPA-PSK/TKIP	•	•	•	•	•	•	•	•	•	\$\$			
WPA2-PSK/AES	•	•	•	•	•	•	•	•	•	\$\$\$			
802.1X	•	•	•	•	•	•	•	•	•				
Rogue AP detection	•	•	•	•	•	•	•	•	•				
WIDS/WIPS													
Wireless Distribution Systems (WDS)	•	•	•	•	•	•	•	•	•				
Repeater	•	•	•	•	•	•	•	•	•				
Point-to-point/multi-point	•	•	•	•	•	•	•	•	•				
Simultaneous bridge/client association	•			•	•	•	•	•	•				
Captive portal		•	•	•	•	•	•	•	•				
VLANs		•	•	•	•	•	•	•	•				
MAC ACL	•	•	•	•	•	•	•	•	•				
802.11e/WMM	•	•	•	•	•	•	•	•	•				
Rate limiting	•	•	•	•	•	•	•	•	•				
Bandwidth management													
Beamforming													
IPv6													
Bandsteering													
WARRANTY													
Warranty	3 years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime				
Product ordering SKU	WN604-100NAS WN604-100AUS WN604-100PES WN604-100UKS	WG103-100NAS WG103-100AUS WG103-100PES WG103-100UKS	WN203-100NAS WN203-100AUS WN203-100PES WN203-100PRS WN203-100UKS	WNAP210-200NAS WNAP210-200AUS WNAP210-200PES WNAP210-200PRS WNAP210-200UKS	WNAP320-100NAS WNAP320-100AUS WNAP320-100PES WNAP320-100PRS WNAP320-100UKS	WNDAP350-100NAS WNDAP350-100AUS WNDAP350-100PES WNDAP350-100UKS	WNDAP360-100NAS WNDAP360-100AUS WNDAP360-100PES WNDAP360-100UKS	WNDAP620-100NAS WNDAP620-100AUS WNDAP620-100PES WNDAP620-100UKS	WNDAP660-100NAS WNDAP660-100AUS WNDAP660-100PES WNDAP660-100UKS	WNDAP660-100NAS WNDAP660-100AUS WNDAP660-100PES WNDAP660-100UKS			
MSRP (NA)	\$	\$\$	\$\$	\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$\$				

** future

* The 3-year and lifetime hardware warranty only covers hardware, fans, internal power supplies, and does not include external power supplies or software. Hardware modifications or customization void the warranty. The warranty is only valid for the original purchaser and cannot be transferred.

NETGEAR, the NETGEAR logo, and ProSAFE are trademarks and/or registered trademarks of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. © 2013 NETGEAR, Inc. All rights reserved.



Promotions

New Wireless Controller Starter Kit



Buy 1 WC7520 Wireless Controller, get 10 FREE WNAP320 Access Points
35% instant savings

WC7523SKT Promotion



Buy 1 WC7520 Wireless Controller, get 3 FREE WNAP360 Access Points
\$3600 instant savings

WC7529SKT Promotion



Buy 1 WC7520 Wireless Controller, get 9 FREE WNDAP360 Access Points
\$3800 instant savings

Wireless Starter Kit Promotion



Buy 2 WNDAP350 Access Points, get 50% off a WMS5316 Wireless Management System
26% savings

Stop Guessing



Get a Free Wireless Site Survey with your purchase of a NETGEAR Wireless solution

www.netgear.com